


# DRIVEN FOR PURITY



#### **DRIVEN FOR PURITY**

Here's food for thought: according to the Bureau of Census Annual Survey of Manufacturers, 57% of a company's sales dollar is spent on materials and capital equipment. Choosing the right equipment is more important than ever, especially in food and beverage processing. An equipment failure is a problem; contamination is a catastrophe. Food processing equipment standards of design and production are more stringent every day and specify today's aggressive high-pressure washdown requirements.


Sumitomo Drive Technologies' Cyclo® and Hyponic® food-grade drives feature a unique rotating, multi-lipped seal that protects drives and keeps food safe. Their fully enclosed construction stands up to aggressive cleaning, including high pressure washing. Food-grade lubricants and severe-duty antimicrobial food-grade powder coating provide additional levels of safety. And like all Sumitomo drives, the food-grade products are built to last, giving you the lowest possible life-cycle cost and the highest level of process purity.

## Cyclo® QuillReducer



## **Hyponic® Quill Reducer**





#### **BEVERAGE MANUFACTURING**

Beverage manufacturing is highly competitive so efficiency matters. Sumitomo Drive Technologies products provide a solution to the tough demands of Beverage processing applications. The grease lubricated, no maintenance, easy to clean products, provide peace of mind and the knowledge that your process will continue to operate at peak performance.

#### **Applications**

| Agitators            | Cyclo 6000          | Cyclo BBB            | Cyclo HBB             |
|----------------------|---------------------|----------------------|-----------------------|
| Batching Equipment   | Cyclo 6000          | Hyponic              |                       |
| Blender              | Cyclo 6000          |                      |                       |
| Conveyors            | Hyponic             | Cyclo 6000           | Cyclo BBB             |
| Chiller              | Cyclo 6000          | Cyclo BBB            |                       |
| Overhead Doors       | Hyponic             | Cyclo 6000           | Altax                 |
| Filler Equipment     | Hyponic             | Cyclo 6000           | IB Precision Gearhead |
| Industrial Robot     | Fine Cyclo          | IBPrecision Gearhead |                       |
| Loader/Unloader      | Cyclo 6000          | Cyclo BBB            |                       |
| Mixing Drum/Mixer    | Cyclo BBB           | Cyclo 6000           |                       |
| Palletizer           | Cyclo 6000          | Servo 6000           | IB Precision Gearhead |
| Packaging Equipment  | Hyponic             | Cyclo 6000           | Astero                |
| Pumps                | Paramax 9000        | Beier Variator       |                       |
| Shrink Wrapping      | IBPrecisionGearhead | Servo 6000           | Astero                |
| Wastewater Treatment | Cyclo BBB           | Cyclo 6000           | Paramax 9000          |



Sumitomo Drive Technologies has a proven track record for manufacturing the most dependable, efficient and long-lasting gear drives available today. We now bring that same reliability - and safety - into the food and beverage industry to meet your needs.

To find out more, contact Sumitomo Drive Technologies or your authorized Sumitomo distributor today.

#### SUMITOMO SPEED REDUCERS FOR FOOD PROCESSING

|   | RIGHT OFFSET LARGE                               |  |   |   |  |  |
|---|--|--|---|---|--|--|
| INLINE  | RIGHT<br>ANGLE                                   | OFFSET<br>PARALLEL                               | PRECISION   | LARGE<br>INDUSTRIAL                                     |  |  |
|   |  | 0  |   |   |  |  |
| Power: 1/8 to 235 HP<br>Ratio: 3:1 to 1,000,000:1         | Power: 1/8 to 40 HP<br>Ratio: 11:1 to 26,000:1 + | Power: 1/8 to 40 HP<br>Ratio: 11:1 to 26,000:1 + | Power: 114 to 4159 lb-in<br>Ratio: 6:1 to 87:1    |   |  |  |
| CYCLO® 6000   | CYCLO® BBB                                       | CYCLO® HBB                                       | SERVO 6000  |   |  |  |
|   | O  |  |   |   |  |  |
| Power: 1/8 to 235 HP<br>Ratio: 3:1 to 1,000,000:1         | Power: 1/8 to 15 HP<br>Ratio: 5:1 to 1,440:1     | Power: 1/4to 300 HP<br>Ratio: 5:1 to 25:1        | Torque: 115 to 1124 lb-in<br>Ratio: 5:1 to 45:1   | Torque: 23,000to5,000,000lb-in<br>Ratio: 6.3:1 to 500:1 |  |  |
| CYCLO® OVERHEAD DRIVE                                     | HYPONIC®   | HSM  | IB PRECISION GEARHEAD                             | PARAMAX® 9000   |  |  |
| Power: 40 to 90 Watts<br>Ratio: 6:1 to 51:1               | Torque: 5.75 to 260.47 lb-in Ratio: 5:1 to 240:1 |  | Torque: 1318 to 54,339 lb-in Ratio: 29:1 to 179:1 |   |  |  |
| ALTAX®  | ASTERO®  |  | FINE CYCLO®                                       |   |  |  |
| Torque: 1.15 to 173.47 lb-in Ratio: 3:1 to 200:1  ASTERO® |  |  |   |   |  |  |

### **Bay Engineers Supplies**

107 Hull Road, Mount Maunganui 3116 Phone: 0800 229 364 Email: PTorders@bayeng.co.nz www.bayengineerssupplies.co.nz